

# NPC-D-5200 Series

## Digital Controllers

A standalone single axis closed loop piezo actuator controller designed to cover a wide range of challenging applications needing the best dynamic performance. There is no compromise; the NPC-D-5200 delivers precision, accuracy and speed.



## Key Features

- Precision capacitive sensor measurement circuit for closed loop operation.
- Update rate of 8.3 micro seconds (120KHz)
- Low electronic noise. The low noise design allows stage position noise as low as a few tens of picometres.
- High power rating, -30 to +150V drive with 160mA continuous current as standard.
- Stage designs incorporate capacitive sensors which give precise positional feedback in closed loop mode delivering high resolution/low noise and high linearity of movement.
- The controller is updated with the position of the stage 120000 times per second. This contributes to high speed positioning accuracy for applications that need high speed movement of the stage.
- A stable system which delivers repeatability of movement with improved precision and accuracy for precise imaging & focusing.
- The high power rating allows stages to be driven at higher maximum speeds with faster step settle times.
- This can be particularly important for longer range stages or stages designed for high load bearing.

## Interfacing

- Analog command and position output +/-10 V
- Digital commands over USB or optional RS232C and Ethernet control interfaces.
- Easy to interface with OEM software using supplied DLL (Dynamic Link Library). In position digital outputs can be used to interface with external devices. Expansion slot to allow custom board for OEM integration.
- Examples of software in C/C++, Python and LabVIEW® provided.
- User programmable Function Playback of custom programmed waveforms such as constant velocity profiles.
- TTL input/output triggers for external control. Programmable when “Function playback” feature used.
- TTL In-Position output to indicate when NanoMechanism reaches the desired/set position (user selectable position accuracy).

## Technical specification

Parameter	Value	Units	Comments
<b>Mechanical</b>			
Size (Width x Depth x Height) Height includes feet Not including protruding components at front and rear of controller	268 x 194 x 70	mm	Additional space required for rear connectors and cables.
Stage Mass	1.8	kg	
Cooling	Fan forced air		Vents on rear and base
<b>Electrical</b>			
Power input	96 to 265 47 to 63	Vrms Hz	Using external supply. Only use approved power supply provides protective earth connection.
DC power input	± 24 ± 0.75@5A	V	Only use Queensgate approved power supply
DC power input connector	4 pin DIN Plus protective earth connection		Rear panel
<b>Connectivity</b>			
USB	2.0 compliant		USB type B connector. Note: power not taken from USB port.
Ethernet	IEEE 802.3		RJ45 connector. Requires a Cat 5 male to male cable. MUST use shielded Ethernet cable.
Analog input command	BNC		Per channel - front panel
Analog Position Monitor output	BNC		Per channel - front panel
“TRIG” input, “TRIG” output, “IN-POS” output and Quadrature Interface	25 pin D-type socket		
Controller Synchronizing signals	9 pin D-type socket		Rear panel
<b>Environmental - Operational</b>			
Temperature	10 to 40	°C	
Relative Humidity	5 to 80	%RH	Non-condensing
<b>Environmental - Storage and Shipping</b>			
Temperature	-20 to 70	°C	
Relative Humidity	0 to 95	%RH	Non-condensing

## Technical specification

Parameter	Value	Units	Comments
General			
Warm up time	40 (typ)	Min	
“ANA I/P” analog input position command per channel	-10 to +10	V	Connector BNC – Single ended MAXIMUM input: ±15V
“ANA I/P” analog input impedance (per channel)	> 50k	Ohms	
“POS MON” analog output position monitor per channel	-10 to +10		Connector BNC – Single ended MAXIMUM input: ±15.5V
“IN- POSITION” Output	Logic “0” < 0.8 Logic “1” 2.4 to 5	V V	15 pin D-Type on rear panel. For OUTPUTS Load impedance: > 1k ohms. MAXIMUM
“TRIG”	Logic “0” < 0.8 Logic “1” 2.4 to 5	V V	output: 5.5V For INPUTS Input impedance: 50 ohms. MAXIMUM input: 5.5V
NanoMechanism interfacing – controller – per channel			
Connector	17W2 D type		Mixed signal connector
HV output swing	-30 to +150	V	Factory set (default)
	-20 to +120		Factory set (optional)
HV drive current	160	mA	Factory set (default)
HV amplifier bandwidth	>50	kHz	
HV amplifier intrinsic noise	0.3	mV	
“ANA I/P” analog output position command	-5 to +5	V	Connector BNC
			Differential input - core +ve
“POS MON” analog output position monitor	-5 to +5	V	Connector BNC Single ended
“READY” output signal	Logic “0” <0.8	V	Connector BNC
	Logic “1” 2.4 to 5	V	

## Ordering information

Product Ref	Description
QGNPC-D-5200	NPC-D-5200 Single axis high performance digital controller.

Owing to continuous development, we reserve the right to introduce improvements and modify specifications without prior notice.

### UNITED KINGDOM

Prior Scientific Instruments Ltd.  
Units 3-4 Fielding Industrial Estate  
Wilbraham Road, Fulbourn  
Cambridge, CB21 5ET  
United Kingdom  
Email: [inquiries@prior.com](mailto:inquiries@prior.com)  
Phone: +44 (0)1223 881711

### U.S.A.

Prior Scientific, Inc.  
80 Reservoir Park Drive  
Rockland, MA. 02370  
U.S.A.  
Email: [info@prior.com](mailto:info@prior.com)  
Phone: +1 781.878.8442

### GERMANY

Prior Scientific Instruments GmbH  
Maria-Pawlowna-Str. 4  
D-07743, Jena, Germany  
Email: [jena@prior.com](mailto:jena@prior.com)  
Phone: +49 (0) 3641 24 20 10

### JAPAN

Kayabacho 3rd Nagaoka Bldg 10F,  
2-7-10, Nihonbashi Kayabacho, Chuo-Ku,  
Tokyo103-0025, Japan  
Email: [info-japan@prior.com](mailto:info-japan@prior.com)  
Phone: 03-5652-8831

### CHINA

Prior Scientific Instruments (Suzhou) Ltd.  
Room 1812, Honghai Building,  
72 Xingdu Street, Suzhou Industrial Park,  
Suzhou, 215000 China  
Email: [info-china@prior.com](mailto:info-china@prior.com)  
Phone: +86 (0)512 6617 5866



[info@microscopeworld.com](mailto:info@microscopeworld.com) | 800-942-0528

